

UFUSION 70 Filtration Media

100% Polyester (PES), 3-layer gradient nonwoven filter medium — 70 g/m².

UFUSION 70 is a 70 g/m² 100% Polyester (PES), 3-layer gradient nonwoven filter medium, thermally bonded, manufactured to consistent technical tolerances for industrial liquid filtration. MD = machine direction, CD = cross direction; figures are indicative average values subject to normal production variation.

UFUSION 70 — Technical Specifications

PARAMETER	VALUE
Fiber / composition	100% Polyester (PES), 3-layer gradient
Bonding	Thermally bonded
Weight (g/m ²) — DIN EN 29073.1	70
Thickness (mm) — DIN EN 29073.2	0,85
Tensile strength MD (N/5cm)	170
Tensile strength CD (N/5cm) — DIN EN 29073.3	150
Elongation MD (%)	35
Elongation CD (%) — DIN EN 29073.3	30
Pore size, largest / many (μ)	● 165 / 60
Air permeability (L/m ² /sek.) — EN ISO 9237	4.200

Union Oiltech

Håndværkervænget 4B · 5700 Svendborg · Danmark · Tlf: +45 7620 8010 · contact@unionoiltech.com · www.unionoiltech.com

© Union Oiltech. All specifications are indicative only and may be subject to change without prior notice.