

## UJet 150 Filtration Media

*100% Polyester (PES) nonwoven filter medium — 150 g/m<sup>2</sup>.*

UJet 150 is a 150 g/m<sup>2</sup> 100% Polyester (PES) nonwoven filter medium, spunlaced, manufactured to consistent technical tolerances for industrial liquid filtration. MD = machine direction, CD = cross direction; figures are indicative average values subject to normal production variation.

### UJet 150 — Technical Specifications

| PARAMETER                                               | VALUE                |
|---------------------------------------------------------|----------------------|
| Fiber / composition                                     | 100% Polyester (PES) |
| Bonding                                                 | Spunlaced            |
| Weight (g/m <sup>2</sup> ) — DIN EN 29073.1             | 150                  |
| Thickness (mm) — DIN EN 29073.2                         | 1,31                 |
| Tensile strength MD (N/5cm)                             | 370                  |
| Tensile strength CD (N/5cm) — DIN EN 29073.3            | 360                  |
| Elongation MD (%)                                       | 45                   |
| Elongation CD (%) — DIN EN 29073.3                      | 75                   |
| Pore size, largest / many (μ)                           | ● 95 / 54            |
| Air permeability (L/m <sup>2</sup> /sek.) — EN ISO 9237 | 2.000                |

#### Union Oiltech

Håndværkervænget 4B · 5700 Svendborg · Danmark · Tlf: +45 7620 8010 · [contact@unionoiltech.com](mailto:contact@unionoiltech.com) · [www.unionoiltech.com](http://www.unionoiltech.com)

© Union Oiltech. All specifications are indicative only and may be subject to change without prior notice.