

UTN 150 K1 Filtration Media

100% Polyester (PES) nonwoven filter medium — 150 g/m².

UTN 150 K1 is a 150 g/m² 100% Polyester (PES) nonwoven filter medium, needled + thermally bonded, manufactured to consistent technical tolerances for industrial liquid filtration. MD = machine direction, CD = cross direction; figures are indicative average values subject to normal production variation.

UTN 150 K1 — Technical Specifications

PARAMETER	VALUE
Fiber / composition	100% Polyester (PES)
Bonding	Needled + thermally bonded
Weight (g/m ²) — DIN EN 29073.1	150
Thickness (mm) — DIN EN 29073.2	1,1
Tensile strength MD (N/5cm)	330
Tensile strength CD (N/5cm) — DIN EN 29073.3	340
Elongation MD (%)	45
Elongation CD (%) — DIN EN 29073.3	55
Pore size, largest / many (μ)	● 89 / 50
Air permeability (L/m ² /sek.) — EN ISO 9237	1.700

Union Oiltech

Håndværkervænget 4B · 5700 Svendborg · Danmark · Tlf: +45 7620 8010 · contact@unionoiltech.com · www.unionoiltech.com

© Union Oiltech. All specifications are indicative only and may be subject to change without prior notice.