



DX1001-T-ATEX1

The DX modular housing arrangement offers a flexible and space conscious solution to integrating our innovative DXO Cartridge to both new and existing systems. We provide up to 12 cartridges as a single unit in a compact and easily maintainable layout with a 'push button' oil sampling port.

The unit can be supplied with a number of standard options to provide an effective conditioning and monitoring package to suit the majority of systems. The flexibility of the unit allows tailoring to a customer's specific requirements.




DXO Cartridge

Dirt capacity:	4.5kg, 0.1 micron
Water absorption, free and bound:	M 2600ml
Material insert:	Cellulose, Polypropylene



Technical Specification




DX1001-T-ATEX1



AC Power	0,25KW , 220-400 VAC, 50/60Hz						
Connection Ports	1/2" BSP In & 3/8" BSP Out						
Flow Indicator	Visual						
Suggested System Volume	4500 litres @ 32cSt						
Flow Rate (varies depending on viscosity, pressure and temperature)	Approx flow at 2.7 bar:	32 cSt	46 cSt	68 cSt	100 cSt	220 cSt	320 cSt
		125 l/min	10 l/min	0.8 l/min	0.6 l/min	0.4 l/min	0.2 l/min
	Oil Volume	4500ltrs	3500ltrs	3000ltrs	2400ltrs	1800ltrs	800ltrs
Micron Rating	0,1 Micron						
Weight	20kg						
Measure [mm]	H 674 x D 300 x L 550						
Material	SS316						
DXO Cartridge	1						
ATEX Zone	II 2 G Ex db h IIC T4 Gb +1°C ≤ Ta ≤ 50°C						



General Arrangement



DIM. /UNIT NO.	DX1001T**	DX1002T**	DX1003T**	DX1004T**	DX1006T**
DIMENSION-A	675mm	908mm	1157mm	908mm	1157mm
DIMENSION-B	550mm	550mm	550mm	825mm	825mm
DIMENSION-C	300mm	300mm	300mm	300mm	300mm
DIMENSION-D	510mm	510mm	510mm	785mm	785mm
EARTH BOSS	M8	M8	M8	M8	M8
INLET PORT	1/2" BSPP	1/2" BSPP	1/2" BSPP	1/2" BSPP	1/2" BSPP
OUTLET PORT	3/8" BSPP	3/8" BSPP	3/8" BSPP	3/8" BSPP	3/8" BSPP
MOUNTING HOLES	4	4	4	8	8
OUTLET PORT POSN	A	A	A	B	B



DX BASE TRAY ELECTRIC MOTOR
DRIVEN - ATEX VERSION

