



DX1006-T-ATEX1

The DX modular housing arrangement offers a flexible and space conscious solution to integrating our innovative DXO Cartridge to both new and existing systems. We provide up to 12 cartridges as a single unit in a compact and easily maintainable layout with a 'push button' oil sampling port

The unit can be supplied with a number of standard options to provide an effective conditioning and monitoring package to suit the majority of systems. The flexibility of the unit allows tailoring to a customer's specific requirements.




DXO Cartridge

Dirt capacity:	4.5kg, 0.1 micron
Water absorption, free and bound:	M 2600ml
Material insert:	Cellulose, Polypropylene



Technical Specification





DX1006-T-ATEX1


AC Power	0,25-0,37KW,220-400 VAC, 50/60Hz						
Connection Ports	1/2" BSP In & 1/2" BSP Out						
Flow Indicator	Visual						
Suggested System Volume	27,000 litres @ 32cSt						
Typical Flow	Approx flow at 2.7 bar:	32 cSt 6.25 l/min	46 cSt 5.0 l/min	68 cSt 4.0 l/min	100 cSt 3.0 l/min	220 cSt 2.0 l/min	320 cSt 1.0 l/min
	Oil Volume	27000ltrs	21000ltrs	18000ltrs	14400ltrs	10800ltrs	4800ltrs
Micron Rating	0,1 Micron						
Weight(kgsl)	55						
Measure [mm]	H 1158 x D 300 x L 825						
Material	SS316						
DXO Cartridge	6						
Atex Zone	II 2 G Ex db h IIC T4 Gb +1°C≤ Ta ≤ 50°C						



General Arrangement



DIM. / UNIT NO.	DX1001T**	DX1002T**	DX1003T**	DX1004T**	DX1006T**
DIMENSION-A	675mm	908mm	1157mm	908mm	1157mm
DIMENSION-B	550mm	550mm	550mm	825mm	825mm
DIMENSION-C	300mm	300mm	300mm	300mm	300mm
DIMENSION-D	510mm	510mm	510mm	785mm	785mm
EARTH BOSS	M8	M8	M8	M8	M8
INLET PORT	1/2" BSPP	1/2" BSPP	1/2" BSPP	1/2" BSPP	1/2" BSPP
OUTLET PORT	3/8" BSPP	3/8" BSPP	3/8" BSPP	3/8" BSPP	3/8" BSPP
MOUNTING HOLES	4	4	4	8	8
OUTLET PORT POSN	A	A	A	B	B



NOTE: A MINIMUM OF 4 No OF MOUNTING HOLES TO BE USED

DX BASE TRAY ELECTRIC MOTOR DRIVEN - ATEX VERSION

